

EU-TYPE EXAMINATION (MODULE B) CERTIFICATE

Radio Equipment Directive (RED) 2014/53/EU

PHOENIX TESTLAB

Notified Body Number 0700



BNetzA-bS-02/51-55

This is to certify that:

PHOENIX TESTLAB did undertake the relevant type examination procedures for the radio equipment identified below which was found to be in compliance with the essential requirements of Radio Equipment Directive (RED) 2014/53/EU subject to any conditions in the annex attached hereto.

Certificate No. 18-212925

Foshan Hicell Technology Co., Ltd Manufacturer

4th Workshop, No.32 of Luowu Road, Shishan Address

Town, Nanhai District, Foshan City, Guangdong

Province, China.

Signal repeater (FTS Torpedo 5); with GSM, **Product Description**

WCDMA and LTE

Hicell / HC17P-5B, HC10-EGSM, HC10-DCS,

HC10-WCDMA, HC10-LTE, HC10-LTE1800,

FTS Torpedo 5

The radio equipment meets the following essential requirements

Article 3.1 a): Health and Safety Conform

Article 3.1 b): Electromagnetic Compatibility Conform

Article 3.2: Effective and Efficient Use of Radio Spectrum Conform

Additional Essential Requirements: Not applicable

Date of issue 2018-11-28 Expiry date: 2023-11-27

This certificate remains valid unless cancelled or revoked, provided the conditions in the attached annex are complied with. The conditions for the validity of this certificate are listed in the Annex.

The attached Annex forms part of this certificate. This certificate consists of 3 pages.

Brand Name / Model Name



Signed by Wayne Hsu Notified Body

> PHOENIX TESTLAB GmbH Köniaswinkel 10 D-32825 Blomberg, Germany www.phoenix-testlab.de

Phone +49(0)5235-9500-24 +49(0)5235-9500-28 notifiedbody@phoenix-testlab.de Date 28 November 2018

Annex

Technical description

Frequency Range GSM 900/1800:

> Uplink: 880 - 915 MHz, 1710 - 1785MHz Downlink: 925 - 960 MHz, 1805 - 1880MHz

UTRA FDD Band I: Uplink: 1920 - 1980 MHz, Downlink: 2110 - 2170 MHz E-UTRA FDD Band 1/3/7/8/20:

Uplink: 1920 - 1980MHz, 1710 - 1785MHz, 2500 - 2570MHz,

880 - 915MHz, 832 - 862MHz

Downlink: 2110 - 2170 MHz, 1805 - 1880 MHz, 2620 - 2690 MHz,

925 - 960 MHz, 791 - 821 MHz

Transmit Power Uplink:17dBm, Downlink: 17dBm

Hardware Version V1 Software Version V1

System Components

Optional Components

Adapter GM25-120200-2A

Input:100-240V, 50/60Hz, 1.0A; Output: 12V/2A (Dongguan Winna Electronic Technology Co., Ltd.)

Outdoor Antenna HC8025-0980, Dipole Antenna, 8.0dBi(Max.) Indoor Antenna HC8025-03360, Dipole Antenna, 3.0dBi(Max.)

Approval documentation

External / Internal Photos Provided, 8 pages

User Manual User Manual of Signal repeater (FTS Torpedo 5), 10 pages

Block Diagram Provided,1 page Circuit Diagram Provided, 7 pages

Operational Description Block Diagram and Theory Circuit Description, 2 pages

PCB Layout Provided, 2 pages Parts Placement Provided, 1 page Parts List Provided, 2 pages

EU Declaration of Conformity 3 pages, November 26, 2018 Explanation of compliance Description in the User Manual

Article 10(2) and Article 10(10)

Further Documents Risk Assessment, 5 pages, November 26, 2018



Applied Standards and Test Reports

Specification	Laboratory	Test Report Number / Version
EN 60950-1:2006+A11:2009+ A1:2010+A12:2011+A2:2013	Shenzhen LCS Compliance Testing Laboratory Ltd.	LCS180813030AS
EN 50385:2002	Shenzhen LCS Compliance Testing Laboratory Ltd.	LCS180813031AEE
ETSI EN 301 489-1 V2.1.1 ETSI EN 301 489-50 V2.1.1	Shenzhen LCS Compliance Testing Laboratory Ltd.	LCS180813031AEA
ETSI EN 303 609 V12.5.1	Shenzhen LCS Compliance Testing Laboratory Ltd.	LCS180813031AEB
ETSI EN 301 908-1 V11.1.1 ETSI EN 301 908-11 V11.1.2	Shenzhen LCS Compliance Testing Laboratory Ltd.	LCS180813031AEC
ETSI EN 301 908-1 V11.1.1 ETSI EN 301 908-15 V11.1.1	Shenzhen LCS Compliance Testing Laboratory Ltd.	LCS180813031AED

Limitations / Restrictions

- The user shall be informed by the person placing the product onto the market if an individual licence may be required for using in EC member states.
- Operating Temperature range is -25 +55 degree Celsius.
- The health assessment was calculated with a separation distance of 50 m, with an antenna gain of external antenna of 8/3 dBi.

Notes

- 1. This certificate will not be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with PHOENIX TESTLAB.
- 2. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/them being placed on the market.
- 3. The manufacturer shall take all measures necessary so that the manufacturing process and its monitoring ensure conformity of the manufactured radio equipment with the approved type described in the EU-type examination certificate and with the requirements of Directive 2014/53/EU that apply to it.
- 4. The manufacturer shall affix the CE marking to each item of radio equipment that is in conformity with the type described in the EU-type examination certificate and satisfies the applicable requirements of the Directive.
- 5. The manufacturer shall draw up a written EU declaration of conformity for each radio equipment type and keep it at the disposal of the national authorities for 10 years after the radio equipment has been placed on the market. The EU declaration of conformity shall identify the radio equipment type for which it has been drawn up. A copy of the EU declaration of conformity shall be made available to the relevant authorities upon request.

